

# Athmer Fingerschutz® - features finger protection

	Feature	NR-25	NR-32 UniSafe®	Comment
<b>Fixing</b>	Invisible clip-on fixing	✗	✓	
	Concealed screws	✗	✓	
	Tamper-proof KLICK-system	✗	✓	
	Property fixing in 2 steps	✗	✓	
<b>Safety within the application</b>	End caps and rounded profile edges	✗	✓	
	Improved fabric gap cover	✗	✓	
	Robust housing & protection of the fabric retaining bar through lateral fabric outlet	✗	✓	
<b>Installation &amp; removal</b>	One-man installation	✓	✓	
	Installation video available online	✗	✓	
	Safe installation / one tool	✗	✓*	* oblong holes for correction on lining profile
	Adaptation to panic fittings on site by predetermined breaking point in the holding bar possible	✗	✓	
	Fast removal for maintenance/cleaning	✗	✓	* possible with utilities
<b>Design &amp; options</b>	Can be bonded to glass	✓	✓	
	XL-variant (fabric pull-out 320mm)	✗	✓	
	better appearance, fits the new „door generation“	✗	✓	
	Uniform design on interior & exterior doors	✗	✓*	* available as w-proof
	W-proof-variant (water proof)	✗	✓	
	Optional ram protection for e.g. hospital - and disabled facilities etc.	✗	✓*	* lengths: 500, 960, 1.923 mm
	Superficial wipe disinfection tested (according to list Robert Koch Institute)	✓	✓	
	Color fabric	black	6 colors to choose, standard black	
Color profile (standard)	C-0	C-0, RAL 7016, RAL 9016 *	more colors on request, * same price	
<b>Application on fire and smoke protection doors</b>	Retrofitting to fire and smoke protection doors	✓	✓	product proven over decades and tested with the leading door manufacturers
	Fast removal on fire and smoke protection doors for fire safety inspection	✗	✓	
<b>Certificates</b>	TÜV-/GS tested EN 16654	✓	✓	
	1 Mio. test cycles	✓	✓	
<b>Technical data</b>	Material profile	Aluminium	Aluminium	
	Installation height	25 mm	32 mm	
	Max. lengths	2.500 mm	3.000 mm	
	Min. lengths	325 mm	325 mm	
	Standard lengths*	1.925 mm	1.925, 2.050 mm	* lengths for standard doors to DIN 18101 with BR2000 and BR2125
	Lengths for power-operated doors**	2.015 mm	2.000, 2.500 mm	** according to EN 16005 - power operated doors - security of use
	Fix lengths	available	available	to be ordered made to measure