

# Schall-Ex® Slide GS-8

## DETAILS

|               |   |
|---------------|---|
| Articlenumber | 1-678   |
| Function      | sliding door                                      |
| Türenmaterial | glass   |
| Application   | interior door                                     |
| Usage         | sound protection, smoke protection, accessibility |

## TECHNICAL DATA

|                      |                              |
|----------------------|------------------------------|
| Width                | 14.6 mm                      |
| Height               | 44.5 mm                      |
| Min. delivery length | 280 mm                       |
| Max. delivery length | 1958 mm                      |
| Thickness of glass   | 8 mm                         |
| Standard length      | 708, 833, 958, 1083, 1208 mm |
| max. travel          | 11 mm                        |
| Actuation            | single-sided                 |
| Actuator             | slide actuator               |
| Outerprofile         | aluminium                    |
| Sealingprofile       | silicone, self-extinguishing |

## FITTING

|        |                                  |
|--------|----------------------------------|
| Fixing | glue<br>glue/ silicon transpaent |
|--------|----------------------------------|

## EXAMINATIONS AND CERTIFICATES

|                          |     |
|--------------------------|-----|
| Sound                    | yes |
| Permanent function IM    | yes |
| Mio Certificate          | yes |
| Leakage rate certificate | yes |
| Barrier free             | yes |
| EPD                      | yes |

