Stadi L-24/20 OS

DETAILS

Articlenumber	1-959
Function	hinged door
Türenmaterial	timber, metal, PVC
Application	exterior door, interior door
Usage	sound protection, smoke protection, fire protection, accessibility

TECHNICAL DATA

Width	24 mm
Height	20 mm
Min. delivery length	230 mm
Max. delivery length	3000 mm
Standard length	750, 900, 1050, 1200 mm
max. travel	16 mm
Actuation	single-sided
Actuator	sliding acutator
removablelnner profile	yes
Outerprofile	aluminium
Surface	plate finish
Sealingprofile	silicone, self-extinguishing



FITTING

Fixing	OS - omega-shaped profile screw under
Espagnolette bolt	yes

EXAMINATIONS AND CERTIFICATES

Permanent function 1M	yes
Mio Certificate	yes
Leakage rate certificate	yes
Corrision test	yes
Corrision	yes
Barrier free	yes

Technical changes reserved / Status 12.10.2024 / Page 1 from 2

Athmer oHG / Sophienhammer / 59757 Arnsberg / Germany
T +49 2932 477-500 / info@athmer.de / **athmer.com**

Stadi L-24/20 OS

UL	yes
EPD	yes
Certifire	yes

Technical changes reserved / Status 12.10.2024 / Page 2 from 2