

Stadi MD-17/17 WS

DETAILS

| | |
|---------------|--|
| Articlenumber | 1-950 |
| Function | hinged door |
| Türenmaterial | timber, metal, PVC |
| Application | exterior door, interior door |
| Usage | sound protection, smoke protection, fire protection, accessibility |

TECHNICAL DATA




| | |
|------------------------|------------------------------|
| Width | 17 mm |
| Height | 17 mm |
| Min. delivery length | 655 mm |
| Max. delivery length | 1600 mm |
| Standard length | 750, 900, 1050, 1200 mm |
| max. travel | 13 mm |
| Actuation | single-sided |
| Actuator | sliding acutator |
| removableInner profile | yes |
| Outerprofile | aluminium |
| Surface | plate finish |
| Sealingprofile | silicone, self-extinguishing |

FITTING

| | |
|-------------------|----------------------|
| Fixing | WS - fixing brackets |
| Espagnolette bolt | yes |


EXAMINATIONS AND CERTIFICATES

| | |
|--------------------------|-----|
| Permanent function IM | yes |
| Mio Certificate | yes |
| Leakage rate certificate | yes |
| Barrier free | yes |
| UL | yes |
| EPD | yes |





MD-17/17 WS



Stadi MD-1 CLASSIFIED NS

